

Index: Q06

Corner: SW 1/16

LAND CORNER RECORD

State of Indiana
Hoosier National Forest

Polk_F16

Township: 7N

Range: 1E

Section: 20 2nd P.M.

County: MONROE CO.

Polk_F16

EXISTING SURVEYS

Original Government Survey				Original Survey Evidence Found			
Year Surveyed:		By:		Date of Search:		By:	
Original Monument:				Monument Found:			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
Subsequent Corner Restoration				Evidence of Subsequent Corner Restoration Found			
Where Filed or Recorded: Surveyors Office Book: Vol.3 Page: 19 Date: 1906 Monument Set:				Year Searched: Monument Found By:			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
Hickory	2"	N25-1/2°E	2-1/2 Lks				
W.Oak	2"	S15-1/2°W	2 Lks				

OTHER EVIDENCE

Describe corner loc. relative to nearby features & dir. to corner location; note fences, roads, etc.	Sketch of Monument
The monument is located 2' east of a north-south fence line, 20' north of a fence running east, on a southeast facing slope, 100' east of a ridge top, 50' south of the crest of a hill, 150' north and 300' west of a ravine	

PERPETUATION RECORD

Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position.													
Southwest 1/16; A 0.25'x0.7' sandstone was found 0.3' above grade with a chiseled "+" on top. This corner was established on a 1906 survey by C.M. Bower, found in Volume 3, page 19.													
Corner Diagram 	Accessories: Describe new BTs & witness objects established to perpetuate existing evidence. 16" Pin Oak N5°W 31.7' 22" White Oak S10°W 6.5' 4" Beech N60°W 21.4'												
Section: 20	<table border="1"> <tr> <td>Corner Recordation:</td> <td></td> <td>Certificate Prepared:</td> <td></td> </tr> <tr> <td>Filed and Recorded in County records:</td> <td></td> <td>Date:</td> <td></td> </tr> <tr> <td>Book:</td> <td></td> <td>Page:</td> <td></td> </tr> </table>	Corner Recordation:		Certificate Prepared:		Filed and Recorded in County records:		Date:		Book:		Page:	
	Corner Recordation:		Certificate Prepared:										
	Filed and Recorded in County records:		Date:										
Book:		Page:											
<table border="1"> <tr> <td>Geodetic Coordinates:</td> <td>Lat./N.</td> <td></td> <td>Long./E.</td> <td></td> </tr> <tr> <td>Edited By:</td> <td>BTR</td> <td>Date Created:</td> <td colspan="2">10/2004</td> </tr> </table>	Geodetic Coordinates:	Lat./N.		Long./E.		Edited By:	BTR	Date Created:	10/2004				
Geodetic Coordinates:	Lat./N.		Long./E.										
Edited By:	BTR	Date Created:	10/2004										

Referenced on BRG survey recorded as InstNo.2005011737.

Accepted by the Monroe County Surveyor Review Board on August 6, 2019.

Index: Q-6 Corner: SW1/16 LAND CORNER RECORD

State of Indiana
Hoosier National Forest

Twnshp: 7N Range: 1E Section: 20 2nd P.M. County Monroe

EXISTING SURVEYS

Original Government Survey

Original Survey Evidence Found

Year Surveyed:		By:		Date of Search:		By:	
Original Monument:	N/A			Monument Found:			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Where Filed or Recorded:	Monroe County Surveyors Office			Year Searched:	10/15/2003	By:	B. Stone
Book: 3	Page: 19	Date: 4/3/1906		Monument Found	3" x 10" sandstone standing firmly 2" above ground with a long + on top		
Monument Set:	Not stated			Species	Diameter	Bearing	Distance
Species	Diameter	Bearing	Distance				
Hickory	2"	N 25 1/2° E	2 1/2° links				
W. Oak	2"	S 15 1/2° W	2 links	W. Oak	20"	S 35° W	1.5 feet

OTHER EVIDENCE

Describe corner loc. relative to nearby features & dir. to corner location; note fences, roads, etc.	Sketch of Monument
The stone is located on the East slope approximately 200 feet east and downslope from the top of a northeast – southwest ridge. North and east fencelines corner 20 feet south of the stone in a 21" White Oak. The end of a dirt roadbed on private land is N 87°E, 22 feet from the stone. A 9" S. Maple with a plastic 6" x 6" brown and white NO HUNTING sign is S 53° W 28.2 feet. The south end of the stone is against the old bearing tree underground and is likely to be destroyed if the tree should fall.	

PERPETUATION RECORD

Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position.

Tied up pink flagging on White Oak and stone.



Corner Diagram	Accessories: Describe new BTs & witness objects established to perpetuate existing evidence.		
	W.Oak (old BT-no tag 20" with 3 strands S 35° W barbwire) 1.5 FT. light blue metal 'L' shaped 5' tall fence post N 11° W 12 Ft.		
	Corner Recordation:	Certificate Prepared:	
	Filed and Recorded in County records:	Date:	
	Book:	Page:	
Section: 20	Geodetic Coordinates:	Lat./N.	Long./E.
	Edited By: Robert J. Stone	Date Created:	10/16/2003